



[ANIMAL HEALTH & WELFARE \(/ADVOCATE/CATEGORY/ANIMAL-HEALTH-WELFARE\)](#)

Studies advance intensive shrimp culture in zero-exchange biofloc raceways

Friday, 1 March 2013

By Tzachi M. Samocha, Ph.D. , André Braga , Vita Magalhães , Bob Advent and Timothy C. Morris

Substantial inputs required to satisfy the high oxygen demand of shrimp, microbes



High-efficiency non-Venturi injectors are providing adequate aeration and water mixing in biofloc raceways.

Losses due to viral disease outbreaks and the potential negative impacts of nutrient-rich water on receiving streams are major challenges for the development of sustainable, biosecure and cost-effective shrimp-farming practices. The use of greenhouse-enclosed, super-intensive, biofloc-dominated, zero-exchange systems may alleviate these problems. However,

operating biofloc systems at high-density production levels over 6 kg/m³ requires substantial inputs to satisfy the high oxygen demand of the shrimp and the microbial communities.

Previous research

Previous studies at the Texas A & M AgriLife Mariculture Lab utilized a pump-driven Venturi to inject air and/or pure oxygen into a central manifold along raceway bottoms to mix and aerate the water, while additional circulation was provided by airlifts and air diffusers. In an effort to reduce production costs for oxygen supplementation and electricity use, the authors began testing low-maintenance non-Venturi injectors, typically used for wastewater treatment, in 100-m³ biofloc raceways.

According to the manufacturer's specifications, the injectors provide a 3:1 air:water ratio. In contrast, the Venturi system provides less than a 1:1 ratio and requires the use of supplemental oxygen at high biomass loading to maintain the desired dissolved-oxygen (D.O.) levels.

The 2010 trial in two, 100-m³ raceways resulted in the production of 6.4 kg shrimp/m³ at harvest, while a subsequent 2011 trial resulted in 8.4 kg/m³. In both cases, the injectors provided adequate mixing throughout the water column, eliminating the need for peripheral aeration devices. Although feed-conversion ratios in both of these trials were unusually high – 2.46 and 1.77, respectively – and some oxygen supplementation was provided to determine if increasing D.O. above 5 mg/L would improve performance during the 2011 trial, the authors were confident that performance could be improved in future production trials.

2012 study

The objectives of the 2012 study were to evaluate the performance of fast-growth shrimp fed a commercial diet formulated for high-density culture systems, and to further evaluate the injector performance in zero-exchange, super-intensive raceways. In addition, primarily through continuous controlled feeding, it was hoped to reduce feed-conversion ratios and feed-related drops in D.O. levels.



Fast-growth shrimp were harvested using a mechanical harvester after a two-month growout.

Trial setup

The 63-day growout trial in 2012 was conducted in two, 100-m³ raceways lined with ethylene propylene diene monomer, a synthetic rubber. To provide aeration and mixing, 14 non-Venturi injectors were positioned parallel to the direction of flow along the bottom of each raceway wall. The system could be operated using a single 2-hp pump, or when conditions such as high biomass and solids loading or low dissolved-oxygen levels dictated, two such pumps working concurrently.

To enable the removal of particulate and dissolved organic matter, each raceway had one additional injector to power a homemade foam fractionator, and a simple 2-m³ conical settling tank. The raceways were initially filled with a mixture of seawater (23 m³), municipal chlorinated freshwater (24 m³) and biofloc-rich water (25 m³) from a previous nursery study.

The shrimp used in the study were a cross produced from Taura-resistant and fast-growth genetic lines. Juveniles of 3.60-g weight were stocked at 500 shrimp/m³.

The shrimp were fed a 35 percent-crude protein diet seven days a week using four belt feeders run continuously in each raceway. On day 7, the raceways were filled to capacity with a mixture of freshwater and saltwater. Initial daily rations were based on an assumed feed-conversion ratio of 1:1.4, growth of 1.5 g/week and mortality of 0.5 percent/week. Rations were later adjusted based on the results of twice-weekly shrimp growth sampling and feed consumption observations.

The raceways were maintained with no water exchange. About 3.32 m³ of freshwater were added weekly to maintain salinity and compensate for water losses associated with operating the foam fractionators and settling tanks. Water temperature, salinity, dissolved oxygen and pH were monitored twice daily. Each raceway was equipped with a dissolved-oxygen monitoring and alarm system. Additional parameters were monitored at regular intervals.



Water quality parameters were regularly monitored during the study. A monitor/alarm system enhanced dissolved oxygen management.

Results

Tables 1 and 2 summarize the daily and weekly water quality indicators. Mean water temperature, salinity, D.O. and pH were 29.60 degrees C, 29.3 ppt, 5.5 mg/L and 7.1, respectively. Total ammonia nitrogen and nitrite nitrogen remained low throughout the study, under 0.6 and 1.5 mg/L, respectively, and nitrate nitrogen levels increased from 67 mg/L at stocking to an average of 309 mg/L at harvest.

Samocha, Mean daily water quality parameters, Table 1

		Mean (\pm S.D.)	Range
Temperature ($^{\circ}$ C)	a.m.	29.34 \pm 0.48	28.16-30.65
Temperature ($^{\circ}$ C)	p.m.	29.81 \pm 0.54	28.38-31.07
Salinity (ppt)	a.m.	29.27 \pm 2.70	25.43-34.70
Salinity (ppt)	p.m.	29.18 \pm 2.71	25.95-34.81
Dissolved oxygen (mg/L)	a.m.	5.65 \pm 0.41	4.92-6.77
Dissolved oxygen (mg/L)	p.m.	5.43 \pm 0.37	4.40-6.33
pH	a.m.	7.07 \pm 0.22	6.54-7.40
pH	p.m.	7.12 \pm 0.24	6.25-7.47

Table 1. Mean daily water quality parameters during a 63-day growout study with juvenile *L. vannamei* in aerated raceways.

Foam fractionators were started on day 8, and the use of the settling tanks began on day 23, when settleable solids reached 23 mL/L in one of the raceways. The flow rate for the foam fractionators was 28.0 L/minute, while in the settling tanks, flows ranged from 8.5 to 20.0 L/minute. Both methods of solids removal were used intermittently. Mean total suspended solids and settleable solids levels were 292 mg/L and 12 mL/L, respectively (Table 2).

Samocha, Mean weekly water quality parameters, Table 2

	Mean (\pm S.D.)	Range
Five-day biological oxygen demand (mg/L)	48.0 \pm 16.9	28.3-87.2
Alkalinity (mg/L)	170.8 \pm 17.7	120.0-201.4
Total suspended solids (mg/L)	292.4 \pm 75.5	137.5-475.0
Settleable solids (mL/L)	12.2 \pm 3.5	2.0-23.0
Volatile suspended solids (mg/L)	193.4 \pm 38.6	127.5-258.3
Turbidity (NTU)	116.2 \pm 42.1	58.3-218.0
Total ammonia nitrogen (mg/L)	0.30 \pm 0.14	0.15-0.59
Nitrite nitrogen (mg/L)	0.36 \pm 0.29	0.10-1.45
Nitrate nitrogen (mg/L)	172.4 \pm 91.7	46.7-364.7

Table 2. Mean weekly water quality parameters during a 63-day growout study with juvenile *L. vannamei* in aerated raceways.

Minor mortality was observed beginning the third week of culture, so supplemental oxygen was provided to alleviate potential stress and stem mortality. The supplemental oxygen had no perceptible effect on mortality, however, and on day 44, when biomass was estimated at about 8.2 kg shrimp/m³, the second 2-hp pump was engaged to increase aeration. Oxygen supplementation was discontinued three days later.

On day 64, shrimp were harvested using a mechanical harvester. Reaching a mean final weight of 22.72 g, the shrimp grew an average of 2.12 g/week and yielded an average of 903 kg/100-m³ raceway (Table 3). At 79.5 percent, survival was moderate. However, mean production levels in the 2012 study were higher than 2011 – 9.03 versus 8.4 kg/m³ – and the feed-conversion ratio was reduced from 1.77 to 1.48.

Samocha, Shrimp performance, Table 3

Raceway	Stocking (shrimp/m ³)	Stocking Weight (g)	Harvest Weight (g)	Weekly Growth (g)	Survival (%)	Yield (kg/m ³)	Feed-Conversion Ratio	Water Use (L/kg)
1	500	3.60	22.76	2.13	80.82	9.20	1.43	139.5
2	500	3.60	22.67	2.12	78.19	8.86	1.53	148.9
Average	Average		22.72	2.12	79.50	9.03	1.48	144.2

Table 3. Shrimp performance following a 63-day growout study with juvenile *L. vannamei* in aerated raceways.

Perspectives

The injectors were able to maintain adequate D.O. levels and mixing for the production of marketable size shrimp in a biofloc-dominated system with a substantial biomass load above 9 kg/m³, maintaining D.O. in the raceways at 83 to 86 percent saturation in most cases.

Although supplemental oxygen was eventually deemed unnecessary in the study, supplementation was reduced by about 15 percent from 2011 levels despite higher biomass. Continuous feeding seems to have eliminated the low-D.O. events observed following hand feeding in the past and may have contributed to improved feed conversion.

The major development of the 2012 study was the reduction of the production cycle from 106 days in 2011 to 63 days due to sustained weekly growth of greater than 2 g. Clearly, the use of shrimp from a fast-growth genetic line can significantly increase the number of potential crops per year and make enclosed biofloc systems more economically viable.

(Editor's Note: This article was originally published in the March/April 2013 print edition of the Global Aquaculture Advocate.)

Authors



TZACHI M. SAMOCHA, PH.D.

Texas A & M AgriLife Research

4301 Waldron Road

Corpus Christi, Texas 78418 USA

t-samochoa@tamu.edu (<mailto:t-samochoa@tamu.edu>)



ANDRÉ BRAGA

Marine Station of Aquaculture

Oceanography Institute

Federal University of Rio Grande

Brazil



VITA MAGALHÃES
Marine Station of Aquaculture
Oceanography Institute
Federal University of Rio Grande
Brazil



BOB ADVENT
a3 All Aqua Aeration
Orlando, Florida, USA



TIMOTHY C. MORRIS

Texas A & M AgriLife Research
4301 Waldron Road
Corpus Christi, Texas 78418 USA

Copyright © 2016–2018
Global Aquaculture Alliance